

# SignLits™ Rechargeable Car Top Signs

Is *Your Sign Lit?*  
1-800-884-1455  
www.SignLits.com

## HTH Car Top Signs Installation Instructions

Tools Needed: Phillips-head screwdriver, Pliers or adjustable wrench, Drill

1. Look on the underside of your car sign to determine which company you purchased your sign from, Cassel or HTH. For Cassel signs see other instruction sheet.
2. Plug in the battery.
  - Your SignLit unit may or may not light at this time depending on the amount of ambient light, state of battery charge and whether or not the unit has been plugged into the charger. Plugging the unit into the charger resets the smart switch on the board.
3. Remove the old light system by unscrewing and lifting off the base plate. Reach into the sign and unplug the old light system.
  - Some **newer signs** have a plastic “bridge” across the opening. This must be removed with a razor or other suitable tool. Continue to Step 4 below.
  - Some **older signs** have screws and some have pop-rivets holding the old light system in. **See Pop-Rivet removal and instructions below.**
4. Plug your new SignLit unit into the cord inside the sign and secure the base plate to the sign.
  - It is easier to connect the plugs by placing the **entire** unit into the sign and resting it there. Reach in with two hands and plug the unit into the sign.
5. Plug the SignLit unit into the charger and charge the batteries.
  - The average recharge time is just over six hours. However, because batteries are shipped in an uncharged state, the trickle charge may turn on early. This will correct itself after a full night on the charger.
  - **Any sign that is used during the day should stay off the charger until the end of the night. Plug the signs into the charger together at the end of the night. This will prolong battery life.**

Turn page over for pop-rivet removal instructions ►  
HTH Signs Page 2

# SignLits™ Rechargeable Car Top Signs

Is *Your* Sign Lit?  
1-800-884-1455  
[www.SignLits.com](http://www.SignLits.com)

## **Pop-Rivet Removal and Installation Instructions: (For older HTH signs with small access plate on underside of sign.)**

1. Remove the access plate from the access hole.
2. Remove all bulbs from inside the sign.
3. Use the enclosed 3/16" drill bit to drill out the center of the rivet (You may need to use a screwdriver to bend up the edge of the pop rivet and hold the rivet with a pair of pliers to prevent it from spinning). Unplug and remove the old lights.
4. Tape the paper template onto the base on the outside of the sign and mark the location of the four holes.
5. Using the 3/16" drill bit again, drill the four mounting holes.
6. Place the **entire** unit into the sign and rest it there. Then reach in with two hands and plug the unit into the sign.
7. With a screwdriver and pliers or a 3/8" wrench, secure your SignLit unit with the four enclosed screws and locknuts.
8. Re-secure the access plate over the access hole.  
**Please Note:** You must cover the access hole. If you have signs with no access plates you can purchase them from your sign supplier Cassel or HTH.
9. Place the unit on the charger overnight and charge the battery.

Questions or Comments please call us at 1-800-884-1455 or e-mail [info@signlits.com](mailto:info@signlits.com).

